

# ADH 758

**ANAEROBIC ADHESIVE  
GEL SEALANT  
MACHINED OR UNMACHINED  
CLOSE-FITTING JOINTS**



## 7 good reasons for using ADH 758


1. ADH 758 is an **anaerobic** mono-component resin.
2. Only hardens in the absence of air, after assembly.
3. Seals surfaces **immediately** (max effectiveness after 24 hours).
4. Maintains a degree of **flexibility**.
5. No risk of excess product blocking vital fluid passageways.
6. The syringe allows for one-handed application (**ease** of application)
7. The syringe ensures that no product is left unused (total extrusion in comparison to the tube). Does not air dry.

## Particularly suitable for use in:



Industry

Recommended by numerous car, HGV, agricultural machinery, construction equipment, maintenance and naval manufacturers for multiple uses such as: gearboxes, water/oil/petrol pumps, hydraulic machinery, raising lids, boxes, oil sumps, compressors...

Characteristics	Instruction for use
Chemical base: dimethacrylate Colour: red Viscosity (Cone/plate): 30000 to 50000 mPas (paste) Density (g/cm <sup>3</sup> ): 1.12 Fluorescent: yes Shelf life in unopened original container (months) : 12 Curing rate: rapid Setting time on M10 steel screw (minutes): 80-160 Setting time on M10 brass bolt/nut (minutes): <30 Gap filling capacity (mm): 0.1 to 0.5 Completely cured after (hours): 24 Breakaway torque according to DIN 54454 standard on steel (Nm): 6 to 13 Shear strength according to DIN 54452 standard (N/mm <sup>2</sup> ): 6 to 13 Temperature range: -50°C/+150°C  For more information, see MSDS.	Apply to the surfaces to be sealed. One 25g syringe provides an 8 meter bead of glue.  <b>TIP: After use, pull back slightly on the plunger to stop the product flow. It is not necessary to replace the white cap</b>  <b>STORAGE PRECAUTIONS</b> Shelf life: 12 months  

GB15102024

**7 en +**  
**BD10: Penetrating**

Our cardboard packaging is recyclable and is manufactured according to FSC forest-friendly guidelines. Our plastics are easily recyclable. This datasheet supersedes previous documents. The information contained in these data sheets is based on our present knowledge and experience and is given as indication only. Under no circumstances does it engage our responsibility in the event of misuse of our products. Non contractual photos and images.



Tél 02 97 54 50 00  
Www.7darmor.fr

