

ANLG

ANTI-FREEZE CLEANER FOR WIND-SCREENS DE-ICING WINDOWS



7 good reasons for using ANLG

- 1. Keeps reservoirs **frost free**.
- 2. Maintains the window-wash circuit during summer.
- 3. Anti-freeze even if diluted.
- 4. High performance cleaner of wind-screens, eliminates greasy film and insects.
- 5. Can be used in all seasons.
- 6. Inert for rubber and paints.
- 7. Does **not require** the use of a scraper.

Particularly suitable for use



Construction



Transport



Can be used in all window-wash reservoir in order to de-ice wind-screens of vehicles and public works engines.

Also allows to clean wind-screens during the inter-season.

Characteristics Instructions for use Summer measurement: 1I of A.N.L.G for 20I of water. Composition alcohols, surfactant. green liquid. Winter measurement: 11 of A.N.L.G for 2I of water for temperatures to Appearance Density 0.86 -10°C. Lowest de-icing temps - 38°C Pour the solution into the reservoir with the relevant dosage. Can be sprayed pure on surfaces to be de-iced. For more information, see MSDS. Treat from top to bottom then let it take effect.

GB14022023/3

7 +

SUNILAV: Industrial degreasing cleaner for bodywork.

This datasheet supersedes previous documents. The information contained in these data sheets is based on our present knowledge and experience and is given as indication only. Under no circumstances does it engage our responsibility in the event of misuse of our products. Non-contractual photos and images.



