

COLMAT

ELASTIC WATERPROOFING SEALANT



7 good reasons for using COLMAT

1. COLMAT is an aqueous dispersion acrylic copolymer used as an **elastic waterproofing sealant**.
2. Forms a **flexible** and waterproof film once dry.
3. Highly **UV** resistant.
4. Adheres to all types of surfaces such as masonry, tiles, slates, fibre cement, chipboard, bitumen coatings, zinc, aluminium, galvanised steel, PVC....
5. Solvent and **CMR free**.
6. Applied in **two coats**, with or without a non-woven mesh for improved resistance.
7. Classified A for **VOC emissions**.

Particularly suitable for use in



Construction



Public buildings

Used in new builds or renovation for waterproofing: traditional roofing, balcony or terrace roofing with limited accessibility (slope $\geq 1\%$), metal roofing, façades, exterior and/or interior walls (cellars, basements, damp rooms...).

Also suitable for repairing tiles, guttering, drains, cracks, or waterproofing repairs....

Protects underground pipes and drains from corrosion.



*Informations sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (des faibles émissions) à C (fortes émissions).

Characteristics	Instructions for use
<p>Aqueous dispersion acrylic copolymer paste pH : 8.50 Density: >1 Solubility: water-soluble Elasticity percentage: 300% Temperature resistance: 100°C Average consumption: 1 to 1.25 kg per m² per coat Conservation: 24 months DO NOT APPLY IN TEMPERATURES >30°C.</p> <p>For more information, see MSDS.</p>	<p>Mix before use. Apply two coats of the undiluted product by roller or brush, leaving 48 hours coats.</p> <p>If you are using this product in combinaison with a mesh for crack-bridging, reinforcing corners or prior to tiling (use a flexible adhesive), unroll the mesh ensuring it sinks into the first coat without wrinkles and bulges. Ensure that the mesh is completely coated.</p> <p>Do not apply in rainy or very hot conditions (temperature above +30°C) and/or in strong winds. Ensure that the surface is clean, dry and free from loose dust/dirt. Clean tools with water before drying.</p> <p>Store in original packaging, out of direct sunlight, in a dry and well-ventilated area. Keep containers closed when not in use. Store at a temperature between +5°C and +30°C.</p>

GB12092022/1

7 +

ALUCOL : Adhesive waterproofing tape

This datasheet supersedes previous documents. The information contained in these data sheets is based on our present knowledge and experience and is given as indication only. Under no circumstances does it engage our responsibility in the event of misuse of our products. Non contractual photos and images.



Tél 02 97 54 50 00
Www.7darmor.fr

7d'Armor