

# COLTOU

## BI-COMPONENT GLUE METHYLMETHACRYLATE



### 7 good reasons for using COLTOU

1. **Universal:** adheres to all materials: metal, glass, plastic, PVC Plexiglas, concrete, natural stone, wood, rubber ...
2. **Rapid:** setting time less than 2 min.
3. High **tensile** strength: 3500N/cm<sup>2</sup>.
4. High **temperature** resistance up to 200°C.
5. Resistant to impacts and vibrations.
6. **Easy** to use: does not require gun application. The mix nozzle gives a perfect blend of the 2 components.
7. **Aesthetic:** translucent blending.

### Particularly suitable for use in



Public buildings



Industry



Services

For assembling on various supports: steel, stainless steel, copper, brass, titanium, ferrite, glass, plastic, Plexiglas, concrete, stone, Aluminium...  
Can replace the riveting.

Characteristics		Instructions for use
<p>Composition: bi-component methylmethacrylate Density: 1.02 Use at: +5°C to +35°C; polymerization faster with the heat. Resistance to temperature: -40°C to +180°C up to 200°C max. Setting speed: &lt;2mn Hardening speed between 2 and 7 mn Volume: 2x12,5ml For more information, see MSDS.</p>		<p>Clean the parts to be glued. Make sure that the 2 components squeeze out equally and then fix on the mixer tip. Squeezes out the necessary quantity. If you stop activating the pistol for more than 1 minute, change the tip and begin again. When the operation is finished, remove the tip and clean cartridge end with a rag taking care not to mix the 2 components and not to create hardened particles in this end which could block the mixer tip. <b>Use without gun application.</b></p>

GB026072015/4

7 +

**ALUCOL** : a use cold adhesive strip for watertightness

This datasheet supersedes previous documents. The information contained in these data sheets is based on our present knowledge and experience and is given as indication only. Under no circumstances does it engage our responsibility in the event of misuse of our products. Non-contractual photos and images.



Tél 02 97 54 50 00  
Www.7darmor.fr

**7d'Armor**