

DECOR 7

WATER-BASED PAINT FOR CONSTRUCTION



7 good reasons for using **DECOR** 7

- 1. Can be used **outside**.
- 2. Excellent adhesion on any surface.
- 3. After drying, gives a micro-porous film and a velvety white matt finish.
- 4. No saponifying effect.
- 5. Practically **odourless** during application,
- 6. Very good resistance to the elements.
- 7. Washable with usual detergents.

Particularly suitable for use in:



Public buildings



Consruction

Applied to surfaces such as cement, smoothed concrete, plaster, fibrocement, old paints.

Characteristics

Composition: Acrylic copolymers in aqueous dispersal.

Density: 1.50 Touch dry: 1 hour

Application a 2nd coat minimum: 6 hours Yield: 6 to 8 m²/kg Colours: White. Colour chart RAL (on inquiry)

Classification AFNOR: NFT36005: family I - class 7 B2

For more information, see MSDS.

Instructions for use

Incompatible with synthetic and cellulose oil paints.

Do not apply at less than 5°C.

Do not use in full sun or on overheated surfaces.

Preparation of surfaces:

Surfaces must be carefully prepared, the old paints must be washed after the elimination of non-adhesive parts.

Application:

Applies with a brush, a roller or a paint gun.

Depending on the porosity of the support, the first coat can be diluted with 5 % of water; after maximum 6 hours of drying, apply the second coat neat.

Clean the material immediately with water.

GB12082022/3

HYDROCIDE: Surface water-proofing product

This datasheet supersedes previous documents. The information contained in these data sheets is based on our present knowledge and experience and is given as indication only. Under no circumstances does it engage our responsibility in the event of misuse of our products. Non-contractual photos and images.



