

# DKAP VERT

**PAINT AND GRAFFITI REMOVER**  
**Non chlorinated**

READY TO USE



## 7 good reasons for using DKAP VERT

1. **Multi-purpose:** DKAP VERT is efficient on all acrylic, glycerophthalic, vinyl, polyurethane, mono and bi-components paints. After action, some paints do not blister but can be removed easily with a scraper.
2. Works on most graffiti and does **not attack** surfaces.
3. **Thixotropic gel**, GREEN DKAP applies to all surfaces even vertical.
4. **Ready and easy to use**, it is time-saving. Adapted to work requiring a good finish.
5. **Neutral** on most surfaces such as wood, concrete, aluminium and all the metals.
6. After action and **complete evaporation** of the product, is totally eliminated either by brushing.
7. Can be used by spraying **neat and cold** but also by brushing.

## Particularly suitable for use:



Public buildings



Construction

Effective on all the acrylic, glycerophthalic, vinyl, polyurethane, mono and two-components paints. Graffiti.

Can be used on most surfaces, wood, concrete, aluminium, metals ...

Characteristics	Instructions for use
<p>Appearance: thixotropic gel Colour: clear but milky Odour: ether pH of the pur product: non measurable. Density: 1.03 g/cm<sup>3</sup></p> <p>Exists in bulk and in spray.</p> <p>For more information, see MSDS.</p>	<p>It is recommended to wear protective gloves and eye protection. Use only in a well-ventilated area. Shake spray before use. up to the ball taking off. Spray at a distance of 20 cm from the surface to be stripped or cleaned. Leave to take effect from few minutes according to the paint thickness and the surface. The appearance of cracks and blisters indicates the product efficiency. Remove the paint with a spatula. The stripped parts can be cleaned with a dry cloth, a spatula, or a wire brush. Repeat this operation if necessary. After use, turn the spray in order to clear it. On fragile plastic material, make a preliminary test on a hidden part of the surface. <b>Do not spray near connected electrical devices. Usable only when the equipment is turned off. Wait 5 min before switching on the devices.</b> Permanent dipping is not advised because of the product's flammability. Emulsionable in water for cleaning tools with water immediately after use.</p>

GB14112014/3

**7 +**

**WYPNET** : Cleaning wipes

This datasheet supersedes previous documents. The information contained in these data sheets is based on our present knowledge and experience and is given as indication only. Under no circumstances does it engage our responsibility in the event of misuse of our products. Non-contractual photos and images.



Tél 02 97 54 50 00  
Www.7darmor.fr

**7d'Armor**