

DRISOL S

NO SLIP ABSORBER AND CLEANER



7 good reasons for using DRISOL S

1. **Highly** absorbent
2. After absorption, it does not become muddy and remains on the floor in the presence if there is a draft.
3. May be used **inside** or **outside**.
4. Total chemical **inertia** and does not disaggregate.
5. Absolutely **odourless**. **Non-flammable**.
6. **Non-abrasive** for floors.
7. Conform to the norm **AFNOR NFP98-190** « Absorbent products for usage on roads ».

Particularly suitable for use in:



Industry



Public buildings



Leisure facilities

Absorbs oils, hydrocarbons, solvents, paints, emulsions....

Non slip, avoids accidents on slippery floors (due to animal or vegetable oils).

Leaves a clean dry floor after cleaning by absorption and sweeping.

Can be used on tiled-floors and painted cement-floors.

Can be used on roads.

| Characteristics | Instructions for use |
|--|---|
| Composition : Diatomaceous earth Colour : red/brown Uncompressed density: 542 kg/m ³ Grain size: 0.3 to 0.7 mm Absorption power for water ⁽¹⁾ : 161% Absorption power for hydrocarbons ⁽¹⁾ : 161% Dust emission rate ⁽²⁾ : 1% Residual adhesive rate ⁽³⁾ : 94% Calcination temperature: 800°C Loss on ignition at 1025°C: 2% <small>(1) Absorption according to the NF T 90-361 standard: uncertainty 5% - (2) Dust emission rate according to the NF P 98-190 standard: uncertainty 2% - (3) Residual cling rate according to the NF P 98-190 standard: uncertainty 5%</small> | Spread a thin layer (several millimetres) on the floor, let it take effect and then simply sweep. Must be destroyed in accordance with absorbed pollutants regulations. Do not used for hydrofluoric acid. For more information, see MSDS. |

GB24042023/6

7 +

WYPSORB : Industrial absorbents, in rolls or sheets

This datasheet supersedes previous documents. The information contained in these data sheets is based on our present knowledge and experience and is given as indication only. Under no circumstances does it engage our responsibility in the event of misuse of our products. Non contractual photos and images.



Tél 02 97 54 50 00
www.7darmor.fr

7d'Armor