

HYDROGLISS

WATERSOLUBLE ANTI-ADHERENT
FOR WELDING POINTS



7 good reasons for using HYDROGLISS

1. Very easy to **apply**. Forms a non-stick that protects metals against welding spatter.
2. **Economical**: No need to scrape off weld spatter.
3. **Easy** to remove with hot water.
4. Does not cause weld **craters**.
5. Does **not give off smoke** when welding.
6. Contains **no** silicone or chlorinated solvent.
7. **Safe**: water-based preparation.

Particularly suitable for use in:



Industry



Construction

Prevents the adherence of soldered joints to sheet iron for part welding operations.
Can be applied to all metallic surfaces.

Characteristics	SPRAY 600	Instructions for use
Composition: aqueous solution of surfactant agents. Density: 1.02 pH at 5 %: 10.3 For more information, see MSDS.		Always use diluted with water, in proportion of 1 volume of HYDROGLISS for 2 volumes of water. Spray the solution evenly on the surface to be protected, then you may weld. Rinse with water with a jet spray.

GB29082018/3

7 +

MANOLAV : Hand-wash gel for workshop

This datasheet supersedes previous documents. The information contained in these data sheets is based on our present knowledge and experience and is given as indication only. Under no circumstances does it engage our responsibility in the event of misuse of our products. Non-contractual photos and images.



Tél 02 97 54 50 00
Www.7darmor.fr

7d'Armor®