

TRAFFIC 200H

REGISTERED ROAD PAINTS
FOR STREET MARKING



7 good reasons for using TRAFFIC 200H

1. Based on **acrylic** resins in solvent phase.
2. **Covers** well. Very good **adhesion** on road surfaces.
3. Dries very **quickly**.
4. Moves with the asphalt.
5. Good **resistance** to traffic.
6. **Temperature** resistant.
7. After drying, **matt finish**.

Particularly suitable for use in



Public building:



Food trade

For road markings such as markings for centre lines, pedestrian crossings, fog lines, directional arrows, car park marking, traffic separation lines, pavement edging....
Applies to bitumen, cement, concrete.

Characteristics	Instructions for use
<p>Composition: acrylic solvent resins. Density: 1.58 Dry matter weight: 76 % Drying time: - clean condition: 5 mn - touch dry: 17 mn Yield: 1.3 m² / kg for 12 to 14 meters linear with a 10 cm wide line. Lifespan: 1,000,000 wheel paths.</p> <p>Registered NF norm: 1RH958S3.</p> <p>For more information, see MSDS.</p>	<p>Apply to temperatures superior to 10°C. Do not apply to wet surfaces. Shake before using. Clean, dust the surface before application. Use neat or diluted with 3 % of D410, depending on the mode of application and the support. Applied with a brush, a paint gun or marking machine. Clean the application equipment before drying with D410.</p>

GB28082018

7 en +

D410 : Thinner for polyurethane and epoxy coat.

This datasheet supersedes previous documents. The information contained in these data sheets is based on our present knowledge and experience and is given as indication only. Under no circumstances does it engage our responsibility in the event of misuse of our products. Non-contractual photos and images.



Tél 02 97 54 50 00
Www.7darmor.fr

7d'Armor