

WYPSORB

NON-WOVEN INDUSTRIAL ABSORBENTS FOR LIQUIDS

Simple, clean and quick.

Exists in oleophilic and oleophilic/
hydrophilic qualities



7 good reasons for using WYPSORB

1. Double action, **preventive or curative**. Improves safety in workshops.
2. Highly **absorbent**.
3. **Simple** to use.
4. WYPSORB **GR50**: Has **aeronautical capacity** certification N°8014.
5. When used, does not emit **dust** and saves cleaning **time**.
6. The waste can be **burnt** easily.
7. Compact, simplified **storage**.

Particularly suitable for use in



Industry



Public buildings



Construction

For liquid removal, they can be used in case of spillage, overflowing, leaks and accidents or pollution.

Characteristics	Instruction for use
Composition: non-woven polypropylene absorbent Exists in different colours. Pre-cut sheets. For more information, see MSDS.	Apply WYPSORB to the surface according to the volume of liquid to be absorbed. Leave until complete absorption of stains. WYPSORB GR50: keep the smooth layer on the top. Waste: can be burnt, refer to the current regulations. WYPSORB melts around 160°C and ignites around 430°C.
GREY (WYPSORB GR50 anti-pilling strengthened roll / WYPSORB GF50 sheets): Oleophilic and hydrophilic: absorbs all liquids on floors, workbenches... WHITE (WYPSORB BR50, roll): Oleophilic: specially adapted to the recycling of hydrocarbons and derivatives on floor and water. YELLOW (WYPSORB JF50): Acids and bases.	

Reference	Works on	Quality	Packaging	Absorption capacity
WYPSORB GR50	All liquids	Grey (40 x 50 cm) ; 320g/30g/m ² Strengthened structure, anti-pilling layer	2 rolls 40m	193l in average (2 rolls)
WYPSORB BR50	Hydrocarbons	White (40 x 50 cm) ; 350g/m ²	2 rolls 40m	241l (2 rolls)
WYPSORB GF50	All liquids	Grey (40 x 50 cm) ; 350g/m ²	100 sheets	104l (100 sheets)
WYPSORB JF50	Acids, bases	Yellow (40 x 50 cm) ; 300g/m ²	50 sheets	41l (50 sheets)

GB25102019/4

7 +

MULBIO NG: Degreasing & tare removal, ready to use.

This datasheet supersedes previous documents. The information contained in these data sheets is based on our present knowledge and experience and is given as indication only. Under no circumstances does it engage our responsibility in the event of misuse of our products. Non-contractual photos and images.



Tél 02 97 54 50 00
Www.7darmor.fr

7d'Armor